



1076 MAX.1000 MAX.240 E40 IP67 WB HALOGEN -O M24-12.5 EARTH-

Floodlight seamless housing of deep drawn stainless steel ASIS 316. The housing is powder coated white and enamelled up to 70-80 µm thickness. The floodlights provide extreme corrosion resistance and high light output.

Item Number	1076093000
GTIN	6947764638442
Stock status	M



Technical specifications

Certificates

Marine Approved	True
-----------------	------

Technical Data

Minimum ambient temperature (°C)	-40
Maximum ambient temperature (°C)	45
IP classification	67

Light Technical Data

Light source	Halogen
Number of lamps	1
Power consumption light source (W)	1000
Lamp base	E40
Light source included	False

Electrical Data

Minimum Voltage -10% (VAC)	220
Maximum voltage +10% (VAC)	240
Minimum frequency -5% (Hz)	50
Maximum frequency +5% (Hz)	60

Optic

Optic	WB - Wide beam
Material of diffuser	Tempered glass
Colour of reflector	Silver
Material of reflector	Aluminium

Housing

Main body material	Stainless steel
Body colour	White
Main body colour name	Traffic white
Main body colour surface	Powder coated
Main body colour RAL code	RAL 9016

Dimensions

Length (mm)	495
Width (mm)	210
Height (mm)	327
Net weight (kg)	6.762

Cable Inlet

Number of cable glands	1
Max cable diameter (mm)	12
Min cable diameter (mm)	10

Logistic Data

Net weight (kg)	6.762
-----------------	-------

Illustrations

